BAUMALIGHT

MINI SKIDSTEERS / MINI DUMPERS

BAUMALIGHT

MINI SKIDSTEERS & MINI DUMPERS



HONDA

Kubola







WHEELED & TRACKED MINI SKIDSTEERS

Manufactured by Baumalight in Wallenstein, Ontario, our line of rugged Mini Skidsteers are designed for versatility. At Baumalight, versatility not only means offering a carrier that can easily navigate in tight spaces, but it also means providing a wide selection of useful tools and attachments.

Powered by either a Honda, Kubota or Yanmar engine, the Baumalight Mini Skidsteers have a hydrostatic drive controlled by true joystick controls. Our Mini Skidsteers come standard with an interchangeable universal mini skidsteer quick attach plate. Baumalight uses a three-pump hydraulic operating system, one for hydraulic flow to run the machine's auxiliary & boom and two pumps for the propulsion systems, one for each drive side. There is a dedicated oil cooler to better manage hydraulic heat generation and the lift cylinders are cushioned at the end of stroke.





FINANCING NOW AVAILABLE!*

All serialized Baumalight Products are now available with convenient purchase financing.

24 - 72 Month Terms Available

* See full Details online

WRL58G WHEELED



WRL58G SPECIFICATIONS

- Honda GX690 Gas Engine 7.84 km/h Travel Speed Single speed motor 22.1 HP (688cc) Joystick Drive Control
- 11 GPM Under no LoadJoystick Boom Control70" Pin Height12.5L Fuel Tank8" Ground Clearance

For a full list of specifications visit www.baumalight.com

TRL536D TRACKED 2-SPEED MOTOR



TRL536D SPECIFICATIONS

Kubota D1105 Diesel Engine 8.8 km/h Travel Speed 2-speed motor 24.5 HP Engine Displacement 1.1L Joystick Drive Control 10.5 GPM Under No LoadJoystick Boom Control76" Pin Height29.25L Fuel Tank with Gauge6.5" Ground ClearanceWider tracks can be installed for less ground compaction.

For a full list of specifications visit www.baumalight.com

WRL58G FEATURES



Honda Gas Engine

The WRL58G model is powered by a reliable 22.1 HP (688cc) Honda GX690 gas engine.



Operating Capacity

The WRL58G model has an operating capacity of 665 lbs (35% of tip capacity) and 760 lbs (35% of tip capacity) with added weight kit.



Ground Speed

The ground speed of the Baumalight Mini Skidsteers is quite impressive with the wheeled model able to reach 7.84 km/h.



High Capacity Fuel Tank The high capacity fuel tank holds 12.5L of fuel allowing you to work longer.



Ground Clearance The WRL58G has a ground clearance of 8 inches.



Stand-In Operator Compartment

For a safer and more comfortable operation, the operator compartment allows you to fully stand inside.

For a full list of specifications and features visit www.baumalight.com

TRL620D TRACKED



TRL620D SPECIFICATIONS

Kubota D1105 Diesel Engine 5.7 km/h Travel Speed Single speed motor 24.5 HP Engine Displacement 1.1L Joystick Drive Control 10.5 GPM Under No Load Joystick Boom Control Standard Self-Leveling 76" Pin Height 40L Fuel Tank with Gauge 6.5" Ground Clearance

For a full list of specifications visit www.baumalight.com



TRL620Y SPECIFICATIONS

Yanmar 3TNV80F Diesel Engine 5.7 km/h Travel Speed Single speed motor 22.8 HP Engine Displacement 1.267 L Joystick Drive Control 11 GPM Under No Load
Joystick Boom Control
Standard Self-Leveling
76" Pin Height
40L Fuel Tank with Gauge
6.5" Ground Clearance

For a full list of specifications visit www.baumalight.com

TRL536D, TRL620D & TRL620Y, TRL630D, TRL630Y FEATURES



Floating Ride-on Platform

The floating ride-on platform provides the operator a smooth ride and improved visibility.



Hydraulic Float The operator can gently skim the attachment along the contour

of the surface without down

pressure or lift.



Self-Leveling

Make sure your load remains level to the ground while you're raising the boom.



Standard Case Drain

Sometimes referred to as a third line, the case drain line will relieve any excess pressure and drain it back to your return line, then into the reservoir.



Far Reach

When you need to reach a far distance, the Baumalight Tracked model is designed for maximum reach. This design feature allows you to load and unload trailers or dump your load from further away.



4-Pin Two Switch Electric Aux Option

As an added option we can offer a boom mounted electric AUX option for the TRL620D/ TRL620Y tracked unit, this can be ordered at the factory or field installed



Diesel Engines

The TRL620D model is powered by a 24.5 HP Kubota D1105 diesel engine. The TRL620Y is powered by a 22.8 HP Yanmar 3TNV80F diesel engine. The increased displacement (1.267 L) of the Yanmar engine equates to a higher torque.

For a full list of specifications and features visit www.baumalight.com



TRL630D SPECIFICATIONS

Kubota D1105 Diesel Engine 8.8 km/h Travel Speed 2-speed motor 24.5 HP Engine Displacement 1.1L Joystick Drive Control 10.5 GPM Under No Load Joystick Boom Control Standard Self-Leveling 76" Pin Height 40L Fuel Tank with Gauge 6.5" Ground Clearance

For a full list of specifications visit www.baumalight.com

TRL630Y SPECIFICATIONS

Yanmar 3TNV80F Diesel Engine 8.8 km/h Travel Speed 2-speed motor 22.8 HP Engine Displacement 1.267 L Joystick Drive Control 11 GPM Under No Load Joystick Boom Control Standard Self-Leveling 76" Pin Height 40L Fuel Tank with Gauge 6.5" Ground Clearance

For a full list of specifications visit www.baumalight.com

BAUMALIG

TRL536D, TRL630D & TRL630Y FEATURES



2-SPEED MOTOR

Max Speed 8.8 km/h

When the job requires less torque and more speed, the 2-speed motor can easily shift from low speed to high speed, reaching a maximum travel speed of 8.8 km/h.

Bulldozing Power

With a 2-speed motor, the low speed engages the high torque, resulting in an impressive amount of bulldozing power.

MINI SKIDSTEER APPLICATIONS

AGRICULTURAL



SNOW REMOVAL



AGRICULTURAL TOOLS



STRAW BLOWER





BALE SPEAR 🕍 MARTATCH



MANURE FORK & GRAPPLE MARTATCH

MANURE FORK MARTATCH

SNOW REMOVAL TOOLS



SNOW BLOWER



DROP SANDER 🚯 BAUMAN



SNOW BLADE MARTATCH



ROTARY SWEEPER MARTATCH

LANDSCAPE & CONSTRUCTION



LANDSCAPE & CONSTRUCTION TOOLS



FLAIL MOWER





STUMP GRINDER



TREE SAW BAUMALIGHT

NEW MINI DUMPERS





SELF-PROPELLED DUMPER

BAUMALIGHT

TRAILER DUMPER

DT515RH SPECIFICATIONS

22.1 HP Honda Gas Engine Hydrostatic Drive Joy stick control Travel Speed: 7.84 KM/h 23.75 L Hydraulic Reservoir Bucket Capacity 0.7 Yard (0.9 Yard Heaped) 7.37" Ground Clearance Wider tracks can be installed for less ground compaction.

DW51QT SPECIFICATIONS

Tow behind Hydraulic AUX Bucket control Bucket Capacity 1 Yard (1.2 Yard Heaped) 7.25" Ground Clearance



Joystick Controls DT515RH only



Stand-in Operator Compartment DT515RH only



7.84 KM/h Ground Speed DT515RH only

For a full list of specifications and features visit www.baumalight.com

ADDITIONAL TOOLS & ATTACHMENTS

SOLD BY EQUIPMENT DEALERS FOR LOCAL SUPPORT



TRAILER DUMPER BAUMALIGHT

PALLET FORK MARTATCH



TRENCHER BAUMALIGHT



TREE PULLER



POWER RAKE





PICK-UP SWEEPER MARTATCH



TILLER 📈 MARTATCH





SNOW BLOWER



TREE SCOOP







4-IN-1 BUCKET MARTATCH

HIGH DUMP BUCKET MARTATCH

For a full list of available tools & attachments visit www.baumalight.com

PRODUCT WARRANTY

Baumalight Mini Skidsteers have a 1 year warranty from the date of purchase. This warranty covers parts and labor, but does not cover misuse, negligence, consequential damage or expenses including loss of profit. The engine is only covered under the original manufacturer's warranty.

To read our full warranty statement, visit Baumalight.com





Check our Baumalight's Deal of the Week to save on Mini Skidsteer Tools!

baumalight.com/product/miniskidsteer-tools-en



Manufactured by: MTB MFG. INC. 4575 Powell Rd. Wallenstein, ON. Canada, N0B 2S0 baumalight.com



